

CSM620N4S236

60V N-Channel Enhancement Mode MOSFET

Voltage	60 V	Current	4 A
----------------	-------------	----------------	------------

Features


- $R_{DS(ON)}$, $V_{GS}@10V$, $I_D@5A < 65m\Omega$
- $R_{DS(ON)}$, $V_{GS}@4.5V$, $I_D@3A < 70m\Omega$
- Advanced Trench Process Technology
- High density cell design for ultra low on-resistance

Mechanical Data

- Case: SOT-23 6L Package
- Terminals: Solderable per MIL-STD-750, Method 2026
- Approx. Weight: 0.0005 ounces, 0.014 grams

SOT-23 6L

Unit : inch(mm)



Maximum Ratings and Thermal Characteristics ($T_A=25^\circ\text{C}$ unless otherwise noted)

PARAMETER		SYMBOL	LIMIT	UNITS
Drain-Source Voltage		V_{DS}	60	V
Gate-Source Voltage		V_{GS}	+20	
Continuous Drain Current (Note 4)	$T_A=25^\circ\text{C}$	I_D	4	A
Pulsed Drain Current (Note 1)		I_{DM}	16	
Power Dissipation	$T_A=25^\circ\text{C}$	P_D	3.1	W
Operating Junction and Storage Temperature Range		T_J, T_{STG}	-55~150	$^\circ\text{C}$
Typical Thermal Resistance Junction to Ambient (Note 4,5)		$R_{\theta JA}$	40.3	$^\circ\text{C/W}$

- Limited only By Maximum Junction Temperature

CSM620N4S236

Electrical Characteristics (T_A=25°C unless otherwise noted)







PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNITS
Static						
Drain-Source Breakdown Voltage	BV _{DSS}	V _{GS} =0V, I _D =250uA	60	-	-	V
Gate Threshold Voltage	V _{GS(th)}	V _{DS} =V _{GS} , I _D =250uA	1	1.8	2.5	
Drain-Source On-State Resistance	R _{DS(on)}	V _{GS} =10V, I _D =5A	-	53	65	mΩ
		V _{GS} =4.5V, I _D =3A	-	61	70	
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =60V, V _{GS} =0V	-	-	1	uA
Gate-Source Leakage Current	I _{GSS}	V _{GS} =±20V, V _{DS} =0V	-	-	±100	nA
Dynamic ^(Note 6)						
Total Gate Charge	Q _g	V _{DS} =48V, I _D =3A, V _{GS} =10V ^(Note 2,3)	-	9.3	-	nC
Gate-Source Charge	Q _{gs}		-	2.2	-	
Gate-Drain Charge	Q _{gd}		-	1.9	-	
Input Capacitance	C _{iss}	V _{DS} =15V, V _{GS} =0V, f=1MHZ	-	509	-	pF
Output Capacitance	C _{oss}		-	47	-	
Reverse Transfer Capacitance	C _{rss}		-	23	-	
Turn-On Delay Time	td(on)	V _{DD} =30V, I _D =3A, V _{GS} =10V, R _G =3.3Ω ^(Note 2,3)	-	3.2	-	ns
Turn-On Rise Time	tr		-	9.7	-	
Turn-Off Delay Time	td(off)		-	18.5	-	
Turn-Off Fall Time	tf		-	6.4	-	
Drain-Source Diode						
Maximum Continuous Drain-Source Diode Forward Current	Is	---	-	-	5	A
Diode Forward Voltage	VSD	Is=1A, VGS=0V	-	0.75	1	V

NOTES :

1. Pulse width≤300us, Duty cycle≤2%.
2. Essentially independent of operating temperature typical characteristics.
3. Repetitive rating, pulse width limited by junction temperature T_{J(MAX)}=150°C. Ratings are based on low frequency and duty cycles to keep initial T_J=25°C.
4. The maximum current rating is package limited.
5. R_{θJA} is the sum of the junction-to-case and case-to-ambient thermal resistance where the case thermal reference is defined as the solder mounting surface of the drain pins. Mounted on a 1 inch² with 2oz.square pad of copper.
6. Guaranteed by design, not subject to production testing.

CSM620N4S236

TYPICAL CHARACTERISTIC CURVES



CSM620N4S236

TYPICAL CHARACTERISTIC CURVES




Fig.7 Gate-Charge Characteristics




Fig.8 Breakdown Voltage Variation vs. Temperature




Fig.9 Threshold Voltage Variation with Temperature




Fig.10 Capacitance vs. Drain-Source Voltage




Fig.11 Maximum Safe Operating Area





Fig.12 Normalized Transient Thermal Impedance

CSM620N4S236

Part No Packing Code Version

Part No Packing Code	Package Type	Packing Type
CSM620N4S236	SOT-23 6L	3K pcs / 7" reel

Packaging Information & Mounting Pad Layout



CSM620N4S236

Notice

Specifications of the products displayed herein are subject to change without notice. CCS or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in CCS terms and conditions of sale for such products, CCS assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of CCS products including liability or warranties relating to fitness for a particular purpose, merchant ability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications.

Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify CCS for any damages resulting from such improper use or sale.