

CSM320N30D3-3

30V N-Channel Enhancement Mode MOSFET

Voltage

30 V

Current

30A



Features

- $R_{DS(ON)}$, $V_{GS}@10V$, $I_D@10A < 3.8m\Omega$
- $R_{DS(ON)}$, $V_{GS}@4.5V$, $I_D@5A < 6m\Omega$
- High switching speed
- Improved dv/dt capability
- Low Gate Charge
- Low reverse transfer capacitance

Mechanical Data

- Case: DFN3333-8L Package
- Terminals : Solderable per MIL-STD-750, Method 2026
- Approx. Weight: 0.001 ounces, 0.03 grams

DFN3333-8L



Maximum Ratings and Thermal Characteristics ($T_A=25^\circ\text{C}$ unless otherwise noted)

PARAMETER		SYMBOL	LIMIT	UNITS
Drain-Source Voltage		V_{DS}	30	V
Gate-Source Voltage		V_{GS}	+20	
Continuous Drain Current	$T_C=25^\circ\text{C}$	I_D	30	A
Pulsed Drain Current ^(Note 1)	$T_C=25^\circ\text{C}$	I_{DM}	120	
Power Dissipation	$T_C=25^\circ\text{C}$	P_D	39	W
Continuous Drain Current	$T_A=25^\circ\text{C}$	I_D	16	A
Power Dissipation	$T_A=25^\circ\text{C}$	P_D	2.0	W
Operating Junction and Storage Temperature Range		T_J, T_{STG}	-55~150	$^\circ\text{C}$
Typical Thermal Resistance ^(Note 4,5)	Junction to Case	$R_{\theta JC}$	3.21	$^\circ\text{C/W}$
	Junction to Ambient	$R_{\theta JA}$	62.5	

- Limited only By Maximum Junction Temperature

CSM320N30D3-3

Electrical Characteristics ($T_A=25^{\circ}\text{C}$ unless otherwise noted)







PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNITS
Static						
Drain-Source Breakdown Voltage	BV _{DSS}	V _{GS} =0V, I _D =250uA	30	-	-	V
Gate Threshold Voltage	V _{GS(th)}	V _{DS} =V _{GS} , I _D =250uA	1	1.6	2.5	
Drain-Source On-State Resistance	R _{DS(on)}	V _{GS} =10V, I _D =10A	-	3.3	3.8	mΩ
		V _{GS} =4.5V, I _D =5A	-	5.0	6	
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =30V, V _{GS} =0V	-	-	1	uA
Gate-Source Leakage Current	I _{GSS}	V _{GS} =±20V, V _{DS} =0V	-	-	±100	nA
Dynamic (Note 6)						
Total Gate Charge	Q _g	V _{DS} =15V, I _D =24A, V _{GS} =4.5V (Note 2,3)	-	23	-	nC
Gate-Source Charge	Q _{gs}		-	8	-	
Gate-Drain Charge	Q _{gd}		-	9	-	
Input Capacitance	C _{iss}	V _{DS} =25V, V _{GS} =0V, f=1.0MHZ	-	2436	-	pF
Output Capacitance	C _{oss}		-	306	-	
Reverse Transfer Capacitance	C _{rss}		-	196	-	
Turn-On Delay Time	td _(on)	V _{DS} =15V, I _D =15A, V _{GS} =10V, R _G =1Ω (Note 2,3)	-	32	-	ns
Turn-On Rise Time	t _r		-	169	-	
Turn-Off Delay Time	td _(off)		-	232	-	
Turn-Off Fall Time	t _f		-	170	-	
Drain-Source Diode						
Maximum Continuous Drain-Source Diode Forward Current	I _s	---	-	-	70	A
Diode Forward Voltage	V _{SD}	I _S =1A, V _{GS} =0V	-	0.66	1.0	V

NOTES :

1. Pulse width $\leq 300\mu s$, Duty cycle $\leq 2\%$
2. Essentially independent of operating temperature typical characteristics
3. Repetitive rating, pulse width limited by junction temperature $T_{J(MAX)}=150^{\circ}\text{C}$. Ratings are based on low frequency and duty cycles to keep initial $T_J=25^{\circ}\text{C}$.
4. The maximum current rating is package limited
5. $R_{\theta JA}$ is the sum of the junction-to-case and case-to-ambient thermal resistance where the case thermal reference is defined as the solder mounting surface of the drain pins. Mounted on a 1 inch² with 2oz.square pad of copper
6. Guaranteed by design, not subject to production testing.






CSM320N30D3-3

TYPICAL CHARACTERISTIC CURVES



CSM320N30D3-3

TYPICAL CHARACTERISTIC CURVES



CSM320N30D3-3

TYPICAL CHARACTERISTIC CURVES




Fig.12 Normalized Transient Thermal Impedance vs. Pulse Width

CSM320N30D3-3


Part No Packing Code Version

Part No Packing Code	Package Type	Packing Type
CSM320N30D3-3	DFN3333-8L	5K pcs / 13" reel

Packaging Information & Mounting Pad Layout


DFN3333-8L Dimension

Unit: inch(mm)



DFN3333-8L Pad Layout

Unit: inch(mm)



CSM320N30D3-3

Notice

Specifications of the products displayed herein are subject to change without notice. CCS or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in CCS terms and conditions of sale for such products, CCS assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of CCS products including liability or warranties relating to fitness for a particular purpose, merchant ability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications.

Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify CCS for any damages resulting from such improper use or sale.