

Transient Voltage Suppressor

Features

- 450 Watts Peak Pulse Power per Line ($t_p = 8/20\mu s$)
- Protects one I/O or power line
- Low Clamping Voltage
- Working Voltage: 3.3 V
- Low Leakage Current
- Response Time is Typically $< 1\text{ ns}$

IEC COMPATIBILITY (EN61000-4)

- IEC 61000-4-2 (ESD) $\pm 30\text{kV}$ (air), $\pm 30\text{kV}$ (contact)
- IEC 61000-4-4 (EFT) 40A (5/50ns)
- IEC 61000-4-5 (Lightning) 30A (8/20 μs)




Mechanical Characteristics

- JEDEC SOD-323 package
- Molding compound flammability rating:
UL 94V-0
- Packaging : Tape and Reel per EIA 481
- RoHS Compliant

Applications

- Laptop Computers
- Cellular Phones
- Digital Cameras
- Personal Digital Assistants (PDAs)

Schematic & PIN Configuration




SOD-323 (Top View)

Transient Voltage Suppressor

Absolute Maximum Rating			
Rating	Symbol	Value	Units
Peak Pulse Power ($t_p=8/20\mu s$)	P_{PP}	450	W
Electrostatic discharge Voltage	V_{ESD}	± 30 (contact)	kV
		± 30 (air)	
Operating Temperature	T_J	-55 to + 125	$^{\circ}C$
Storage Temperature	T_{STG}	-55 to +150	$^{\circ}C$

Electrical Parameters (T=25 $^{\circ}C$)

Symbol	Parameter
I_{PP}	Reverse Peak Pulse Current
V_C	Clamping Voltage @ I_{PP}
V_{RWM}	Working Peak Reverse Voltage
I_R	Reverse Leakage Current @ V_{RWM}
V_{BR}	Breakdown Voltage @ I_T
I_T	Test Current
I_F	Forward Current
V_F	Forward Voltage @ I_F



Electrical Characteristics

CSE3.3BCS323						
Parameter	Symbol	Conditions	Minimum	Typical	Maximum	Units
Reverse Stand-Off Voltage	V_{RWM}				3.3	V
Reverse Breakdown Voltage	V_{BR}	$I_T=1mA$	4.0			V
Reverse Leakage Current	I_R	$V_{RWM}=3.3V, T=25^{\circ}C$			200	nA
Peak Pulse Current	I_{PP}	$t_p=8/20\mu s$			30	A
Clamping Voltage	V_C	$I_{PP}=30A, t_p=8/20\mu s$			15	V
Junction Capacitance	C_j	$V_R = 0V, f = 1MHz$		37	40	pF

Typical Characteristics

Figure 1: Peak Pulse Power vs. Pulse Time




Figure 2: Power Derating Curve




Figure 3: Clamping Voltage vs. Peak Pulse Current




Figure 4: Normalized Junction Capacitance vs. Reverse Voltage








Figure 5: Pulse Waveform



Transient Voltage Suppressor

Outline Drawing – SOD-323

PACKAGE OUTLINE 	 SOD-323 DIMENSIONS <table><tr><th rowspan="2">SYMBOL</th><th colspan="2">MILLIMETER</th><th colspan="2">INCHES</th></tr><tr><th>MIN</th><th>MAX</th><th>MIN</th><th>MAX</th></tr><tr><td>A</td><td>1.60</td><td>1.80</td><td>0.063</td><td>0.071</td></tr><tr><td>B</td><td>0.25</td><td>0.35</td><td>0.010</td><td>0.014</td></tr><tr><td>C</td><td>2.50</td><td>2.70</td><td>0.098</td><td>0.106</td></tr><tr><td>D</td><td>0.00</td><td>1.00</td><td>0.000</td><td>0.039</td></tr><tr><td>E</td><td>1.20</td><td>1.40</td><td>0.047</td><td>0.055</td></tr><tr><td>F</td><td>0.08</td><td>0.15</td><td>0.003</td><td>0.006</td></tr><tr><td>L</td><td colspan="2">0.475 REF</td><td colspan="2">0.019REF</td></tr><tr><td>L1</td><td>0.25</td><td>0.40</td><td>0.010</td><td>0.016</td></tr><tr><td>H</td><td>0.00</td><td>0.10</td><td>0.000</td><td>0.004</td></tr></table>	SYMBOL	MILLIMETER		INCHES		MIN	MAX	MIN	MAX	A	1.60	1.80	0.063	0.071	B	0.25	0.35	0.010	0.014	C	2.50	2.70	0.098	0.106	D	0.00	1.00	0.000	0.039	E	1.20	1.40	0.047	0.055	F	0.08	0.15	0.003	0.006	L	0.475 REF		0.019REF		L1	0.25	0.40	0.010	0.016	H	0.00	0.10	0.000	0.004
SYMBOL	MILLIMETER		INCHES																																																				
	MIN	MAX	MIN	MAX																																																			
A	1.60	1.80	0.063	0.071																																																			
B	0.25	0.35	0.010	0.014																																																			
C	2.50	2.70	0.098	0.106																																																			
D	0.00	1.00	0.000	0.039																																																			
E	1.20	1.40	0.047	0.055																																																			
F	0.08	0.15	0.003	0.006																																																			
L	0.475 REF		0.019REF																																																				
L1	0.25	0.40	0.010	0.016																																																			
H	0.00	0.10	0.000	0.004																																																			
MOUNTING PAD 	Notes 1. Controlling Dimensions in Millimeters. 2. Dimensions are exclusive of mold flash and metal burrs.																																																						

Package Information

Qty: 3k/Reel

Notice

Specifications of the products displayed herein are subject to change without notice. CCS or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in CCS terms and conditions of sale for such products, CCS assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of CCS products including liability or warranties relating to fitness for a particular purpose, merchant ability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications.

Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify CCS for any damages resulting from such improper use or sale.