

CSM212N2S23

20V N-Channel Enhancement Mode MOSFET

Voltage 20 V **Current** 2A

Features


- $R_{DS(ON)}$, $V_{GS}@10V$, $I_D@4.4A < 48m\Omega$
- $R_{DS(ON)}$, $V_{GS}@4.5V$, $I_D@2.8A < 65m\Omega$
- Advanced Trench Process Technology
- Specially Designed for switch Load, PWM applications, and solid-state relays relay

Mechanical Data

- Case: SOT-23 Package
- Terminals: Solderable per MIL-STD-750, Method 2026
- Approx. Weight: 0.0003 ounces, 0.0084 grams

SOT-23

Unit: inch(mm)



Maximum Ratings and Thermal Characteristics ($T_A=25^{\circ}C$ unless otherwise noted)

| PARAMETER | | SYMBOL | LIMIT | UNITS |
|--|----------------------|-----------------------------------|---------|--------|
| Drain-Source Voltage | | V _{DS} | 20 | V |
| Gate-Source Voltage | | V _{GS} | ±12 | V |
| Continuous Drain Current | | I _D | 2 | A |
| Pulsed Drain Current | | I _{DM} | 8 | A |
| Power Dissipation | T _a =25°C | P _D | 1.25 | W |
| | Derate above 25°C | | 10 | mW/ °C |
| Operating Junction and Storage Temperature Range | | T _J , T _{STG} | -55~150 | °C |
| Typical Thermal resistance | | R _{θJA} | 100 | °C/W |
| - Junction to Ambient ^(Note 3) | | | | |

CSM212N2S23

Electrical Characteristics ($T_A=25^{\circ}\text{C}$ unless otherwise noted)

| PARAMETER | SYMBOL | TEST CONDITION | MIN. | TYP. | MAX. | UNITS |
|---|---------------------|---|------|------|------|-------|
| Static | | | | | | |
| Drain-Source Breakdown Voltage | BV _{DSS} | V _{GS} =0V, I _D =250uA | 20 | - | - | V |
| Gate Threshold Voltage | V _{GS(th)} | V _{DS} =V _{GS} , I _D =250uA | 1.0 | 1.37 | 2.1 | V |
| Drain-Source On-State Resistance | R _{DS(on)} | V _{GS} =10V, I _D =4.4A | - | 35 | 48 | mΩ |
| | | V _{GS} =4.5V, I _D =2.8A | - | 51 | 65 | |
| Zero Gate Voltage Drain Current | I _{DSS} | V _{DS} =20V, V _{GS} =0V | - | 0.01 | 1 | uA |
| Gate-Source Leakage Current | I _{GSS} | V _{GS} =±12V, V _{DS} =0V | - | ±10 | ±100 | nA |
| Dynamic | | | | | | |
| Total Gate Charge | Q _g | V _{DS} =15V, I _D =2A, V _{GS} =10V (Note 1,2) | - | 5.8 | - | nC |
| Gate-Source Charge | Q _{gs} | | - | 1 | - | |
| Gate-Drain Charge | Q _{gd} | | - | 1 | - | |
| Input Capacitance | C _{iss} | V _{DS} =15V, V _{GS} =0V, f=1.0MHZ | - | 235 | - | pF |
| Output Capacitance | C _{oss} | | - | 36 | - | |
| Reverse Transfer Capacitance | C _{rss} | | - | 24 | - | |
| Switching | | | | | | |
| Turn-On Delay Time | td _(on) | V _{DD} =15V, I _D =2A, V _{GS} =10V, R _G =6Ω (Note 1,2) | - | 3 | - | ns |
| Turn-On Rise Time | tr | | - | 39 | - | |
| Turn-Off Delay Time | td _(off) | | - | 23 | - | |
| Turn-Off Fall Time | tf | | - | 28 | - | |
| Drain-Source Diode | | | | | | |
| Maximum Continuous Drain-Source Diode Forward Current | I _S | --- | - | - | 1.5 | A |
| Diode Forward Voltage | V _{SD} | I _S =1.0A, V _{GS} =0V | - | 0.77 | 1.2 | V |

NOTES :

1. Pulse width $\leq 300\mu s$, Duty cycle $\leq 2\%$
2. Essentially independent of operating temperature typical characteristics.
3. $R_{\theta JA}$ is the sum of the junction-to-case and case-to-ambient thermal resistance where the case thermal reference is defined as the solder mounting surface of the drain pins mounted on a 1 inch FR-4 with 2oz. square pad of copper
4. The maximum current rating is package limited

CSM212N2S23

TYPICAL CHARACTERISTIC CURVES




Fig.1 On-Region Characteristics




Fig.2 Transfer Characteristics




Fig.3 On-Resistance vs. Drain Current




Fig.4 On-Resistance vs. Junction temperature




Fig.5 On-Resistance Variation with VGS.




Fig.6 Body Diode Characteristics

CSM212N2S23

TYPICAL CHARACTERISTIC CURVES




Fig.7 Gate-Charge Characteristics




Fig.8 Threshold Voltage Variation with Temperature.





Fig.9 Capacitance vs. Drain-Source Voltage.

CSM212N2S23

PART NO PACKING CODE VERSION

| Part No Packing Code | Package Type | Packing type |
|----------------------|--------------|------------------|
| CSM212N2S23 | SOT-23 | 3K pcs / 7" reel |

MOUNTING PAD LAYOUT



CSM212N2S23

Notice

Specifications of the products displayed herein are subject to change without notice. CCS or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in CCS terms and conditions of sale for such products, CCS assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of CCS products including liability or warranties relating to fitness for a particular purpose, merchant ability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications.

Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify CCS for any damages resulting from such improper use or sale.