


### Features

- 300 Watts peak pulse power ( $t_p = 8/20\mu s$ )
- Bidirectional and unidirectional configurations
- Solid-state silicon-avalanche technology
- Low clamping voltage
- Low leakage current
- IEC 61000-4-2  $\pm 30kV$  contact  $\pm 30kV$  air
- IEC 61000-4-4 (EFT) 40A(5/50ns)
- IEC 61000-4-5 (Lightning) 6A(8/20 $\mu s$ )





### Applications

- Dataline
- Automatic Teller Machines
- Net works
- Power line

### Mechanical Data

- SOT-23 package
- Molding compound flammability rating: UL 94V-0
- Packaging: Tape and Reel
- RoHS/WEEE Compliant

### Schematic & PIN Configuration



## Absolute Maximum Rating


| Rating                                                         | Symbol    | Value          | Units |
|----------------------------------------------------------------|-----------|----------------|-------|
| Peak Pulse Power ( $t_p=8/20\mu s$ )                           | $P_{PP}$  | 300            | Watts |
| Peak Pulse Current ( $t_p=8/20\mu s$ ) (note1)                 | $I_{PP}$  | 6              | A     |
| ESD per IEC 61000-4-2 (Air)<br>ESD per IEC 61000-4-2 (Contact) | $V_{ESD}$ | 30<br>30       | kV    |
| Lead Soldering Temperature                                     | $T_L$     | 260(10seconds) | °C    |
| Junction Temperature                                           | $T_J$     | -55 to + 125   | °C    |
| Storage Temperature                                            | $T_{stg}$ | -55 to + 125   | °C    |

## Electrical Characteristics

| Parameter                 | Symbol    | Conditions                                 | Min  | Typical | Max  | Units   |
|---------------------------|-----------|--------------------------------------------|------|---------|------|---------|
| Reverse Stand-Off Voltage | $V_{RWM}$ |                                            |      |         | 24   | V       |
| Reverse Breakdown Voltage | $V_{BR}$  | $I_T=1mA$                                  | 26.7 | 30.0    | 34.0 | V       |
| Reverse Leakage Current   | $I_R$     | $V_{RWM}=24V, T=25^\circ C$                |      | 0.1     | 0.5  | $\mu A$ |
| Peak Pulse Current        | $I_{PP}$  | $t_p=8/20\mu s$                            |      |         | 6    | A       |
| Clamping Voltage          | $V_C$     | $I_{PP}=6A, t_p=8/20\mu s$                 |      |         | 44   | V       |
| Junction Capacitance      | $C_j$     | $V_R=0V, f=1MHz$<br>(Pin1 、 Pin2 to Pin 3) |      | 30      | 35   | pF      |

## Electrical Parameters (TA = 25°C unless otherwise noted)


| Symbol    | Parameter                                   |
|-----------|---------------------------------------------|
| $I_{PP}$  | Maximum Reverse Peak Pulse Current          |
| $V_C$     | Clamping Voltage @ $I_{PP}$                 |
| $V_{RWM}$ | Working Peak Reverse Voltage                |
| $I_R$     | Maximum Reverse Leakage Current @ $V_{RWM}$ |
| $V_{BR}$  | Breakdown Voltage @ $I_T$                   |
| $I_T$     | Test Current                                |
|           |                                             |
|           |                                             |




Note: 8/20 $\mu s$  pulse waveform.

## Typical Characteristics


**Figure 1: Peak Pulse Power vs. Pulse Time**




**Figure 2: Power Derating Curve**




**Figure 3: Pulse Waveform**




**Figure 4: Clamping Voltage vs. Ipp**



**Figure 5: Peak Pulse Power Vs Junction Temperature**



Outline Drawing – SOT-23



| SYMBOL | DIMENSIONS |       |           |       |
|--------|------------|-------|-----------|-------|
|        | MILLIMETER |       | INCHES    |       |
|        | MIN        | MAX   | MIN       | MAX   |
| A      | 0.900      | 1.150 | 0.035     | 0.045 |
| A1     | 0.000      | 0.100 | 0.000     | 0.004 |
| A2     | 0.900      | 1.050 | 0.035     | 0.041 |
| D      | 2.800      | 3.000 | 0.110     | 0.118 |
| b      | 0.300      | 0.500 | 0.012     | 0.020 |
| E      | 2.250      | 2.550 | 0.089     | 0.100 |
| E1     | 1.200      | 1.400 | 0.047     | 0.055 |
| e      | 0.950 BSC  |       | 0.037 BSC |       |
| L      | 0.300      | 0.500 | 0.012     | 0.020 |
| θ      | 0          | 8°    | 0         | 8°    |

CCS Semiconductor and CSemi are trademarks of Semiconductor Components Industries, CCS Semiconductor reserves the right to make changes without further notice to any products herein. CCS Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does CCS Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. CCS Semiconductor does not convey any license under its patent rights nor the rights of others.