


### Features

- Output Current of 1.5A
- Output Voltage Tolerance of 5%
- Internal thermal overload protection
- Internal Short-Circuit Limited
- No External Component
- Output Voltage 5.0V, 6V, 8V, 9V, 10V, 12V, 15V, 18V, 24V
- Offer in plastic TO-252, TO-220 & TO-263

### Applications

- Post regulator for switching DC/DC converter
- Bias supply for analog circuits



**TO263 (S)**

1. Input
2. GND
3. Output

### Ordering Information

Device	Operating Voltage	Temp.
7805	7 to 20	0 to 125 °C
7806	8 to 20	0 to 125 °C
7808	10.5 to 23	0 to 125 °C
7809	11.5 to 24	0 to 125 °C
7810	12.5 to 25	0 to 125 °C
7812	14.5 to 27	0 to 125 °C
7815	17.5 to 30	0 to 125 °C
7818	20.5 to 33	0 to 125 °C
7824	26.5 to 39	0 to 125 °C

TO-220 (T)  
 TO-263 (S)  
 TO-252 (D)

### Absolute Maximum Rating

Parameter	78XX	Unit
Input Voltage	40 35	V
Operating Free-Air, Case, Virtual Junction Temp.	0 to 125	°C
Storage Temperature Range	-65 to 150	
Lead temperature 1.6 mm from case for sec.	260	

### Electrical Characteristics (7805)

( $V_I=10V$ ,  $I_O=500mA$ ,  $0^\circ C \leq T_J \leq 125^\circ C$ , unless otherwise specified. (Note 1))

Parameter	Symbol	Conditions	MIN	TYP	MAX	UNIT
Output Voltage	$V_O$	$T_J = 25^\circ C$	4.8	5.0	5.2	V
Line Regulation	$\Delta V_O$	$V_I = 7V$ to $25V$ $T_J = 25^\circ C$		3	100	mV
		$V_I = 8V$ to $12V$ $T_J = 25^\circ C$		1	50	
Load Regulation	$\Delta V_O$	$I_O = 5mA$ to $1.5A$ , $25^\circ C$		15	100	mV
		$I_O = 250mA$ to $750mA$ , $25^\circ C$		5	50	
Ripple Rejection	RR	$V_I = 8V$ to $18V$ , $f=120Hz$	62	78		dB
Output Noise Voltage	$V_N$	$F=10Hz$ to $100Hz$ $T_J = 25^\circ C$		40		$\mu V$
Dropout Voltage	$V_D$	$T_J = 25^\circ C$		2.0		V
Quiescent Current		$T_J = 25^\circ C$		4.2	8	mA
Quiescent Current Change	$\Delta I_Q$	$V_I = 7V$ to $25V$ , $T_J = 25^\circ C$			1.3	mA
		$I_O = 5mA$ to $1A$ , $T_J = 25^\circ C$			0.5	

### Electrical Characteristics (7806)

( $V_I=11V$ ,  $I_O=500mA$ ,  $0^\circ C \leq T_J \leq 125^\circ C$ , unless otherwise specified. (Note 1))

Parameter	Symbol	Conditions	MIN	TYP	MAX	UNIT
Output Voltage	$V_O$	$T_J = 25^\circ C$	5.75	6.0	6.25	V
Line Regulation	$\Delta V_O$	$V_I = 8V$ to $25V$ $T_J = 25^\circ C$		5	120	mV
		$V_I = 9V$ to $25V$ $T_J = 25^\circ C$		1.5	60	
Load Regulation	$\Delta V_O$	$I_O = 5mA$ to $1.5A$ , $25^\circ C$		14	120	mV
		$I_O = 250mA$ to $750mA$ , $25^\circ C$		4	60	
Ripple Rejection	RR	$V_I = 9V$ to $19V$ , $f=120Hz$	59	75		dB
Output Noise Voltage	$V_N$	$F=10Hz$ to $100Hz$ $T_J = 25^\circ C$		45		$\mu V$
Dropout Voltage	$V_D$	$T_J = 25^\circ C$		2.0		V
Quiescent Current		$T_J = 25^\circ C$		4.3	8.0	mA
Quiescent Current Change	$\Delta I_Q$	$V_I = 8V$ to $25V$ , $T_J = 25^\circ C$			1.3	mA
		$I_O = 5mA$ to $1A$ , $T_J = 25^\circ C$			0.5	

**Electrical Characteristics (7808)**

( $V_I=14V$ ,  $I_O=500mA$ ,  $0^\circ C \leq T_J \leq 125^\circ C$ , unless otherwise specified. (Note 1))

Parameter	Symbol	Conditions	MIN	TYP	MAX	UNIT
Output Voltage	$V_O$	$T_J = 25^\circ C$	7.7	8.0	8.3	V
Line Regulation	$\Delta V_O$	$V_I = 10.5V$ to $25V$ $T_J = 25^\circ C$		6	160	mV
		$V_I = 11V$ to $17V$ $T_J = 25^\circ C$		2	80	
Load Regulation	$\Delta V_O$	$I_O = 5mA$ to $1.5A$ , $25^\circ C$		12	160	mV
		$I_O = 250mA$ to $750mA$ , $25^\circ C$		4	80	
Ripple Rejection	RR	$V_I = 11.5V$ to $21.5V$ , $f=120Hz$	55	72		dB
Output Noise Voltage	$V_N$	$F = 10Hz$ to $100Hz$ $T_J = 25^\circ C$		52		$\mu V$
Dropout Voltage	$V_D$	$T_J = 25^\circ C$		2.0		V
Quiescent Current		$T_J = 25^\circ C$		4.3	8	mA
Quiescent Current Change	$\Delta I_Q$	$V_I = 10.5V$ to $25V$ , $T_J = 25^\circ C$			1	mA
		$I_O = 5mA$ to $1A$ , $T_J = 25^\circ C$			0.5	

**Electrical Characteristics (7809)**

( $V_I=16V$ ,  $I_O=500mA$ ,  $0^\circ C \leq T_J \leq 125^\circ C$ , unless otherwise specified. (Note 1))

Parameter	Symbol	Conditions	MIN	TYP	MAX	UNIT
Output Voltage	$V_O$	$T_J = 25^\circ C$	8.6	9.0	9.40	V
Line Regulation	$\Delta V_O$	$V_I = 11.5V$ to $27V$ $T_J = 25^\circ C$		7	180	mV
		$V_I = 13V$ to $19V$ $T_J = 25^\circ C$		2	90	
Load Regulation	$\Delta V_O$	$I_O = 5mA$ to $1.5A$ , $25^\circ C$		12	180	mV
		$I_O = 250mA$ to $750mA$ , $25^\circ C$		4	90	
Ripple Rejection	RR	$V_I = 12V$ to $19V$ , $f=120Hz$	55	70		dB
Output Noise Voltage	$V_N$	$F = 10Hz$ to $100Hz$ $T_J = 25^\circ C$		60		$\mu V$
Dropout Voltage	$V_D$	$T_J = 25^\circ C$		2.0		V
Quiescent Current		$T_J = 25^\circ C$		4.3	8	mA
Quiescent Current Change	$\Delta I_Q$	$V_I = 11.5V$ to $27V$ , $T_J = 25^\circ C$			1.0	mA
		$I_O = 5mA$ to $1A$ , $T_J = 25^\circ C$			0.5	

**Electrical Characteristics (7810)**

( $V_I=17V$ ,  $I_O=500mA$ ,  $0^\circ C \leq T_J \leq 125^\circ C$ , , unless otherwise specified. (Note 1)

Parameter	Symbol	Conditions	MIN	TYP	MAX	UNIT
Output Voltage	$V_O$	$T_J = 25^\circ C$	9.6	10	10.4	V
Line Regulation	$\Delta V_O$	$V_I = 12.5V$ to $28V$ $T_J = 25^\circ C$		7	200	mV
		$V_I = 14V$ to $20V$ $T_J = 25^\circ C$		2	100	
Load Regulation	$\Delta V_O$	$I_O = 5mA$ to $1.5A$ , $25^\circ C$		12	200	mV
		$I_O = 250mA$ to $750mA$ , $25^\circ C$		4	100	
Ripple Rejection	RR	$V_I = 13V$ to $23V$ , $f=120Hz$	55	71		dB
Output Noise Voltage	$V_N$	$F = 10Hz$ to $100Hz$ $T_J = 25^\circ C$		70		$\mu V$
Dropout Voltage	$V_D$	$T_J = 25^\circ C$		2.0		V
Quiescent Current		$T_J = 25^\circ C$		4.3	8	mA
Quiescent Current Change	$\Delta I_Q$	$V_I = 12.5V$ to $28V$ , $T_J = 25^\circ C$			1.0	mA
		$I_O = 5mA$ to $1A$ , $T_J = 25^\circ C$			0.5	

**Electrical Characteristics (7812)**

( $V_I=19V$ ,  $I_O=500mA$ ,  $0^\circ C \leq T_J \leq 125^\circ C$ , unless otherwise specified. (Note 1)

Parameter	Symbol	Conditions	MIN	TYP	MAX	UNIT
Output Voltage	$V_O$	$T_J = 25^\circ C$	11.50	12	12.5	V
Line Regulation	$\Delta V_O$	$V_I = 14.5V$ to $30V$ $T_J = 25^\circ C$		10	240	mV
		$V_I = 16V$ to $22V$ $T_J = 25^\circ C$		3.0	120	
Load Regulation	$\Delta V_O$	$I_O = 5mA$ to $1.5A$ , $25^\circ C$		12	240	mV
		$I_O = 250mA$ to $750mA$ , $25^\circ C$		4	120	
Ripple Rejection	RR	$V_I = 15V$ to $25V$ , $f=120Hz$	55	71		dB
Output Noise Voltage	$V_N$	$F = 10Hz$ to $100Hz$ $T_J = 25^\circ C$		75		$\mu V$
Dropout Voltage	$V_D$	$T_J = 25^\circ C$		2.0		V
Quiescent Current		$T_J = 25^\circ C$		4.3	8.0	mA
Quiescent Current Change	$\Delta I_Q$	$V_I = 14.5V$ to $30V$ , $T_J = 25^\circ C$			1.0	mA
		$I_O = 5mA$ to $1A$ , $T_J = 25^\circ C$			0.5	

**Electrical Characteristics (7815)**

( $V_I=23V$ ,  $I_O=500mA$ ,  $0^{\circ}C \leq T_J \leq 125^{\circ}C$ , unless otherwise specified. (Note 1))

Parameter	Symbol	Conditions	MIN	TYP	MAX	UNIT
Output Voltage	$V_O$	$T_J = 25^{\circ}C$	14.40	15	15.60	V
Line Regulation	$\Delta V_O$	$V_I = 17.5V$ to $30V$ $T_J = 25^{\circ}C$		12	300	mV
		$V_I = 20V$ to $26V$ $T_J = 25^{\circ}C$		3	150	
Load Regulation	$\Delta V_O$	$I_O = 5mA$ to $1.5A$ , $25^{\circ}C$		12	300	mV
		$I_O = 250mA$ to $750mA$ , $25^{\circ}C$		4	150	
Ripple Rejection	RR	$V_I = 18.5V$ to $28.5V$ , $f=120Hz$	54	70		dB
Output Noise Voltage	$V_N$	$F=10Hz$ to $100Hz$ $T_J = 25^{\circ}C$		90		$\mu V$
Dropout Voltage	$V_D$	$T_J = 25^{\circ}C$		2.0		V
Quiescent Current		$T_J = 25^{\circ}C$		4.3	8.0	mA
Quiescent Current Change	$\Delta I_Q$	$V_I = 17.5V$ to $30V$ , $T_J = 25^{\circ}C$			1.0	mA
		$I_O = 5mA$ to $1A$ , $T_J = 25^{\circ}C$			0.5	

**Electrical Characteristics (7818)**


( $V_I=27V$ ,  $I_O=500mA$ ,  $0^{\circ}C \leq T_J \leq 125^{\circ}C$ , unless otherwise specified. (Note 1))

Parameter	Symbol	Conditions	MIN	TYP	MAX	UNIT
Output Voltage	$V_O$	$T_J = 25^{\circ}C$	17.30	18	18.7	V
Line Regulation	$\Delta V_O$	$V_I = 21V$ to $33V$ $T_J = 25^{\circ}C$		15	360	mV
		$V_I = 24V$ to $33V$ $T_J = 25^{\circ}C$		5	180	
Load Regulation	$\Delta V_O$	$I_O = 5mA$ to $1.5A$ , $25^{\circ}C$		12	360	mV
		$I_O = 250mA$ to $750mA$ , $25^{\circ}C$		4	180	
Ripple Rejection	RR	$V_I = 22V$ to $32V$ , $f=120Hz$	53	69		dB
Output Noise Voltage	$V_N$	$F=10Hz$ to $100Hz$ $T_J = 25^{\circ}C$		110		$\mu V$
Dropout Voltage	$V_D$	$T_J = 25^{\circ}C$		2.0		V
Quiescent Current		$T_J = 25^{\circ}C$		4.5	8.0	mA
Quiescent Current Change	$\Delta I_Q$	$V_I = 21V$ to $33V$ , $T_J = 25^{\circ}C$			1.0	mA
		$I_O = 5mA$ to $1A$ , $T_J = 25^{\circ}C$			0.5	

**Electrical Characteristics (7824)**

 ( $V_I=33V$ ,  $I_O=500mA$ ,  $0^{\circ}C \leq T_J \leq 125^{\circ}C$ , unless otherwise specified. (Note 1))

Parameter	Symbol	Conditions	MIN	TYP	MAX	UNIT
Output Voltage	$V_O$	$T_J = 25^{\circ}C$	23	24	25	V
Line Regulation	$\Delta V_O$	$V_I = 27V$ to $38V$ , $T_J = 25^{\circ}C$		18	480	mV
		$V_I = 30V$ to $36V$ , $T_J = 25^{\circ}C$		6	240	
Load Regulation	$\Delta V_O$	$I_O = 5mA$ to $1.5A$ , $25^{\circ}C$		12	480	mV
		$I_O = 250mA$ to $750mA$ , $25^{\circ}C$		4	240	
Ripple Rejection	RR	$V_I = 28V$ to $38V$ , $f=120Hz$	50	66		dB
Output Noise Voltage	$V_N$	$F= 10Hz$ to $100Hz$ , $T_J = 25^{\circ}C$		170		$\mu V$
Dropout Voltage	$V_D$	$T_J = 25^{\circ}C$		2.0		V
Quiescent Current		$T_J = 25^{\circ}C$		4.6	8.0	mA
Quiescent Current Change	$\Delta I_Q$	$V_I = 27V$ to $38V$ , $T_J = 25^{\circ}C$			1.0	mA
		$I_O = 5mA$ to $1.0A$ , $T_J = 25^{\circ}C$			0.5	

CCS Semiconductor and  are trademarks of Semiconductor Components Industries, CCS Semiconductor reserves the right to make changes without further notice to any products herein. CCS Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does CCS Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. CCS Semiconductor does not convey any license under its patent rights nor the rights of others.