


Features

- 150 Watts peak pulse power ($t_p = 8/20\mu s$)
- Transient protection for high speed data lines to IEC 61000-4-2 (ESD) $\pm 15kV$ (air), $\pm 8kV$ (contact) IEC 61000-4-4 (EFT) 40A(5/50ns)
- Protects One Power or I/O Port
- Low leakage current
- Low operating and clamping voltages
- Solid-state silicon avalanche technology



Applications

- Cell Phone Handsets and Accessories
- Microprocessor based equipment
- Portable Instrumentation
- Personal Digital Assistant(PDA)

Maximum Rating @ $T_a=25^{\circ}C$ unless otherwise specified


Symbol	Parameter	Ratings	Units
P_{PK}	Peak Pulse Power ($t_p = 8/20\mu s$)	150	Watts
T_L	Lead Soldering Temperature	260(10sec)	$^{\circ}C$
T_J	Operating Temperature	-55 to +125	$^{\circ}C$
T_{STG}	Storage Temperature	-55 to +150	$^{\circ}C$

Electrical Characteristics@ Ta=25°C unless otherwise


Parameter	VRWM @IR		VBR@ImA	VC@1A	VC@IPP		CJ
	V	μA	V	V	V	A	pF
		MAX	MIN	MAX	MAX		MAX
ESD5Z3V3	3	1	4.8	8.8	14.5	12	120
ESD5Z5V0	5	1	6.2	9.8	15.6	10	100
ESD5Z7V0	7	1	8.2	13	19.6	8	80
ESD5Z12V	12	1	13.3	19	32.8	6	60
ESD5Z15V	15	1	16.7	24	36.5	5	50
ESD5Z24V	24	1	26.7	43	56.8	3	30
ESD5Z36V	36	1	38.6	55	78.5	3	25

Typical Characteristics@ Ta=25°C unless otherwise specified



Non-Repetitive Peak Pulse Power vs. Pulse Time



Power Derating Curve




Pulse Waveform



Soldering Parameters





Reflow Condition		Fb – Free assembly
Pre Heat	- Temperature Min ($T_{s(Min)}$)	150°C
	- Temperature Max ($T_{s(Max)}$)	200°C
	- Time (Min to max) (t_s)	60 – 180 secs
Average ramp up rate (Liquidus) Temp (T_L) to peak		3°C/second Max
$T_{s(Max)}$ to T_L - Ramp-up Rate		3°C/second Max
Reflow	- Temperature (T_L) (Liquidus)	217°C
	- Temperature (t_L)	60 – 150 seconds
Peak Temperature (T_p)		250 ^{+0/-5} °C
Time within 5°C of actual peak Temperature (t_p)		20 – 40 seconds
Ramp-down Rate		6°C/second Max
Time 25°C to peak Temperature (T_p)		8 minutes Max.
Do not exceed		260°C



Package Outline

Plastic surface mounted package

SOD523



DIMENSIONS (mm are the original dimensions)

UNIT	A	b _P	c	D	E	H _E	v
mm	0.65 0.58	0.34 0.26	0.17 0.11	1.25 1.15	0.85 0.75	1.65 1.55	0.1